



**AMENDMENTS TO THE CLAIMS**

1. (Currently amended) A method for implementing a customized instance of a dynamic interactive voice system for a customer, the dynamic interactive voice system having a database, the method comprising:

configuring a call flow that incorporates a plurality of call flow nodes of different node types, the different node types comprising a plurality of standard nodes and a plurality of preprogrammed designer tool kit modules, each designer tool kit module having its own a database that is separate from the dynamic interactive database, at least one of the designer tool kit modules being a call library application, at least one of the designer tool kit modules being a zip code locator module, and at least one of the designer tool kit modules being a voice forms module;

storing the call flow in association with an identification of the customer;

activating the stored call flow in response to a call to a dialed number associated with the customized instance; and

processing at least one call flow node of the stored call flow.

2. (Original) The method for implementing the customized instance according to claim 1, in which configuring the customer call flow further comprises:

displaying at least one data field relating to at least one parameter of each call flow node at a display terminal, the at least one parameter directing processing of the associated call flow node; and

receiving data defining the at least one parameter from the display terminal.

3. (Original) The method for implementing the customized instance according to

claim 2, in which the at least one parameter comprises an identification number of a selected call flow node of the plurality of call flow nodes to be processed after the at least one call flow node.

4. (Original) The method for implementing the customized instance according to claim 3, in which an initial call flow node of the plurality of call flow nodes comprises a menu node.

5. (Previously presented) The method for implementing the customized instance according to claim 1, in which the standard node comprises one of a menu node, a transfer node, a vocabulary node and an end node.

6. (Previously presented) The method for implementing the customized instance according to claim 1, in which the designer tool kit module comprises one of an automatic attendant interactive voice response functionality and a names directory interactive voice response functionality.

7. (Currently amended) A method for configuring for a customer a customized instance of a dynamic interactive voice application without altering the underlying computer programming of the dynamic interactive voice application, the customized instance being executed in response to calls to a telephone number of the customer, the method comprising:

storing a plurality of nodes executable by the dynamic interactive voice application, each node of the plurality of nodes being one of a plurality of predetermined node types comprising at least one standard node type included in the dynamic interactive voice application and a plurality of preprogrammed feature specific node types, at least one of

the feature specific node types being a call library application that allows a caller to access pre-established messages from a customer maintained library, and at least one of the feature specific node types being a zip code locator module;

displaying a data field for each node at a graphical user interface, the data field corresponding to a variable parameter associated with the node type of the node; and

receiving data via the graphical user interface corresponding to the data field of each node, the data indicating a predetermined function to be performed by the corresponding node and establishing a call flow of the customized instance, the dynamic interactive voice application executing the predetermined function in accordance with the call flow regardless of the node type.

8. (Original) The method for configuring the customized instance of a dynamic interactive voice application according to claim 7, in which the data entered in the data field of each node comprises at least an identification number of a second node of the plurality of nodes, indicating that the call flow proceeds to the second node.

9. (Original) The method for configuring the customized instance of a dynamic interactive voice application according to claim 7, the at least one node type comprising one of a menu node type, a vocabulary node type and a transfer node type.

10. (Currently amended) The method for configuring the customized instance of a dynamic interactive voice application according to claim 9, the data entered in the data field of a node from the menu node type comprising an identification number of a second node of the plurality of nodes, indicating that the call flow proceed to the second node when the a caller selects a menu item number corresponding to the identification number of the

second node.

11. (Original) The method for configuring the customized instance of a dynamic interactive voice application according to claim 9, the data entered in the data field of a node from the vocabulary node type comprising a predetermined vocabulary tag to be spoken via a voice generator to a terminal of a caller.

12. (Original) The method for configuring the customized instance of a dynamic interactive voice application according to claim 9, the data entered in the data field of a node from the transfer node type comprising a transfer destination code.

13. (Previously presented) The method for configuring the customized instance of a dynamic interactive voice application according to claim 7, the feature specific node type comprising one of an auto attendant interactive voice response functionality, and a names directory interactive voice response functionality.

14. (Currently amended) A system for implementing a customized instance of a dynamic interactive voice system for a customer, the system comprising:

an interactive voice response (IVR) system comprising a preprogrammed IVR application;

a user terminal that enables assembly of a call flow associated with the customized instance, the call flow incorporating a plurality of call flow nodes within the IVR application, the plurality of call flow nodes comprising a plurality of node types that are interchangeable for call flow incorporation, the different node types comprising at least one standard node and a plurality of preprogrammed designer tool kit modules, each designer tool kit module having its own database, at least one of the designer tool kit modules being a zip code

P21784.A09

locator module, and at least one of the designer tool kit modules being a voice forms module; and

a database that stores the call flow in association with at least one port of a plurality of ports of the IVR system;

the IVR system initiating the IVR application in response to an incoming call received at the at least one port and executing the plurality of call nodes as directed by the call flow associated with the at least one port in the database.

15. (Original) The system for implementing the customized instance according to claim 14, the at least one port of the IVR system being associated with a telephone number of the customer, so that the incoming call is directed by a public switched telephone network to the at least one port based on calls to the customer telephone number.

16. (Currently amended) A system for configuring for a customer a customized instance of a dynamic interactive voice application without altering the underlying computer programming of the dynamic interactive voice application, the customized instance being executed in response to calls to a telephone number of the customer, the system comprising:

an interactive voice response (IVR) system configured to execute a preprogrammed IVR application;

a database that stores a plurality of nodes executable by the IVR application according to a call flow of the customized instance, each node of the plurality of nodes being one of a plurality of predetermined node types comprising at least one standard node type dependant on the IVR application and a plurality of preprogrammed feature specific

node types, each feature specific node type having its own database, at least one of the feature specific node types being a call library application, at least one of the feature specific node types being a zip code locator module, and at least one of the feature specific node types being a voice forms module; and

a graphical user interface that receives the plurality of nodes from the database and displays a data field for each node corresponding to a variable parameter associated with the node type of the node, the graphical user interface receiving data, input by a user, corresponding to the data field of each node, the data indicating a predetermined function to be performed by the corresponding node and establishing the call flow of the customized instance, the IVR application executing the predetermined function in accordance with the call flow regardless of the node type.

17. (Currently amended) A computer readable medium for storing a computer program that controls configuration and operation of an interactive voice response (IVR) system for a customer according to a preprogrammed IVR application, the computer readable medium comprising:

a configuration source code segment that enables configuring a call flow that incorporates a plurality of call flow nodes within a framework of the IVR application, the plurality of call flow nodes comprising a plurality of different node types that are interchangeable in the framework of the IVR application, the plurality of different node types comprising at least one standard node and a plurality of preprogrammed designer tool kit modules, each designer tool kit module having its own database, at least one of the designer tool kit modules being a call library application, at least one of the designer tool

kit modules being a zip code locator module, and at least one of the designer tool kit modules being a voice forms module;

a memory that stores the call flow in association with at least one port of the IVR system, which corresponds to a telephone number of the customer; and

an IVR source code segment that retrieves the call flow from the memory in response to an incoming call to the at least one port and executes the IVR application as directed by the call flow.

18. (Original) The computer readable medium for storing the computer program according to claim 17, further comprising:

an administrative source code segment that is initiated by an escape code received by the IVR source code segment via the incoming call and that enables at least one of an addition, a deletion and a change of an administrative variable associated with the call flow.

19. (Original) The computer readable medium for storing the computer program according to claim 18, in which the administrative variable comprises one of a telephone extension number and a voice announcement.

20. (Currently amended) A computer readable medium for storing a computer program that enables configuration for a customer of a customized instance of a dynamic interactive voice application without altering the underlying computer programming of the dynamic interactive voice application, the computer readable medium comprising:

a storing source code segment that stores a plurality of nodes executable by the dynamic interactive voice application, each node of the plurality of nodes being one of a plurality of predetermined node types comprising at least one standard node type included

in the dynamic interactive voice application and a plurality of preprogrammed feature specific node types, each feature specific node type having its own database, at least one of the feature specific node types being a call library application, and at least one of the feature specific node types being a voice forms module; and

an interfacing source code segment that displays a data field for each node at a display terminal, the data field corresponding to a variable parameter associated with the node type of the node, and that receives data via the display terminal corresponding to the data field of each node, the data indicating a predetermined function to be performed by the corresponding node and establishing a call flow of the customized instance, the dynamic interactive voice application executing the predetermined function in response to an incoming call to a telephone number of the customer in accordance with the call flow, regardless of the node type.

21. (Previously presented) The method of claim 1, in which each designer tool kit module has different tools for different audiences.

22. (Previously presented) The method of claim 7, in which each feature specific node type has different tools for different audiences.

23. (Previously presented) The system of claim 14, in which each designer tool kit module has different tools for different audiences.

24. (Previously presented) The system of claim 16, in which each feature specific node type has different tools for different audiences.

25. (Previously presented) The medium of claim 17, in which each designer tool kit module has different tools for different audiences.



P21784.A09

26. (Previously presented) The medium of claim 20, in which each feature specific node type has different tools for different audiences.